

MEMBER OF DOCOD



S200 plus Series Continuous Inkjet Printer

S200 plus series continuous small character inkjet printer is designed for high quality printing and improving production line effectively.

Its print head adopts Independent structure design, and the stainless steel chassis, which can maintain reliable operation in harsh production environment as well as improve the production line effectively.

Print Head



The nozzle valve adopts direct sealing nozzle hole structure, effectively prevent the ink leakage.

Ink System



Double-head pump design makes more stable and durable. White ink machine has double mixing system to prevent the pigment ink precipitation.

Main Hardware



The main board with newest structure has superior performance of function and stability, and the EHT is dustproof and waterproof, better to deal with the harsh and complex environment.


External Interface



With grade of IP68, the interface not only supports RS232, network port, but also the counter reset, information control and other functions.



Print Head



650 mm



Front view

Side view



Screen



Technical Parameters

Printing Parameters

Print Head Duct 3m/6m

Nozzle Specifications 40u、50u、60u、75u、85u

Printing Height 2~20mm **Printing Distance** 3~30mm **Printing Lines** 1~5 lines **Printing Speed** 384m/min

Counter More than 20 independent counters Ink Color Black, Red, Blue, Green, White, Invisible

High adhesion, Migration resistance, Ink Type

High temperature resistance, Special for glass,

Permeability, Food grade, Oil resistance

5×6L 7×6L 7×10L 9×8L 9×11L Font

11×11L 16×16L 24×24L 32×32L 11×11B 16×16B 24×24B 32×32B

Printing Material Carton, Plastic, Metal, Boarding, Pipe, Stone, Cable,

Glass, Electronic components, Auto parts,

Industrial chemical packaging, Medical / Food / Gift box

Print Content Text,Time, Date(Julian Year), Logo, Shift, SN, Dynamic

> Barcode/QR Code, Dynamic Serial Data, Dynamic Database(Additional content can be added as required)

Machine Parameters

Operating System Embedded Linux security operating system 10.1-inch color display, industrial touch screen Display Screen

Network port, USB, RS232 Communication Interface

Protection Level IP55

Power Parameters Input 100-240V AC

Rated Power 150W Memory 256M

Machine Material 304 stainless steel

Machine Specifications 447mm×242mm×650mm(Length×width×height)

Working Environment Temperature 0-45°C/ Humidity 30-70%Rh

Related Certification RoHS、CE、BIS

Net Weight 30kg

Main Hardware American TI AM3358 industrial grade CPU,

American Xilinx Spartan-6 industrial grade

External Interface Optical sensor, Encoder, Reverse and upside down

> control, Signal light alarm output, Serial number output control, External printing information selection

Support Language Support more than 40 national languages (Chinese,

> English, Arabic, Danish, German, Russian, French, Finnish, Korean, Japanese, Spanish, Italian, etc.)

Applications



Codpad

Guangzhou Codpad e-tech Company Limited

https://www.docod-group.com/ sales@docod.com.cn

Add: Building 2, NO.27, Hejing Road, LiWan District, Guangzhou, China

Printing Samples

	urig Samples
5X6	ABCDEFG 12345 5X5
7X6	ABCDEFG 12345 6×7
7X10	ABCDEFG 12345 10×7
9X8	ABCDEFG 12345 8X9
9X11	ABCDEFG 12345 11X9
11X11L	ABCDEFG 12345 11X11
11X11B	ABCDEFG 12345 11×11B
16X16L	ABCDEFG1234516X16L
16X16B	ABCDEFG1234516X16B
24X24L	ABCDE12345 24X24L
24X24B	ABCDE12345 24X24B
32X32L	ABCDE1234532X32L
32X32B	ABCDE1234532X32B
5X6(5lines)	
7X6(2lines)	QWERTYUIOP 20210414 1234567890 20210414
7X6(3lines)	QUERTYUIOP 20210414 1234567890 20220414 ABCOEFCHIJKLMNOP0123456789
7X6(4lines)	ABCDEFCHIJKLMNOPO 12345678900WERTYU 20345678900WERTYU 20345678543210P010YTR
LOGO	\$₩₽♥♥♥♥
Tower	COCOMFO-NW4NOV
DM Codes	
Barcodes	