



S1000 Series Continuous Inkjet Printer

S1000 series continuous small character inkjet printer is designed for high quality printing and improving production line effectively.

Its print head adopts modular design, and the stainless steel chassis, which can maintain reliable operation in harsh production environment as well as improve the production line effectively.

Print Head




The nozzle valve adopts direct sealing nozzle hole structure, effectively prevent the ink leakage.

Ink System



Single print head and recovery diaphragm pump design makes more stable and durable.

Main Hardware



The main board with newest structure has superior performance of function and stability, and the EHT is dustproof and waterproof, better to deal with the harsh and complex environment.


External Interface



With grade of IP68, the interface not only supports RS232, network port, but also the counter reset, information control and other functions.

🔥 S1000 Series

Print Head



240 mm

Front view



550 mm

400 mm

Side view



250 mm

Screen



10.1-inch

🔥 Technical Parameters

Printing Parameters

Print Head Duct	3m/6m
Nozzle Specifications	50u、60u、75u
Printing Height	2~20mm
Printing Distance	3~30mm
Printing Lines	1~3 lines
Printing Speed	576m/min (5x6 dot matrix, single line, 0.5mm dot spacing)
Counter	More than 20 independent counters
Ink Color	Black, Red, Blue, Green, White, Invisible
Ink Type	High adhesion, Migration resistance, High temperature resistance, Special for glass, Permeability, Food grade, Oil resistance
Font	5x6L 7x6L 7x10L 9x8L 9x11L 11x11L 16x16L 24x24L 11x11B 16x16B 24x24B
Printing Material	Carton, Plastic, Metal, Boarding, Pipe, Stone, Cable, Glass, Electronic components, Auto parts, Industrial chemical packaging, Medical / Food / Gift box
Print Content	Text, Time, Date (Julian Year), Logo, Shift, SN, Dynamic Barcode/QR Code, Dynamic Serial Data, Dynamic Database (Additional content can be added as required)

Machine Parameters

Operating System	Embedded Linux security operating system
Display Screen	10.1-inch color display, industrial touch screen
Communication Interface	Network port, USB, RS232
Protection Level	IP55
Power Parameters	Input 100-240V AC
Rated power	150W
Memory	256M
Machine Material	304 stainless steel
Machine Specifications	400mmx250mmx550mm (Lengthxwidthxheight)
Working Environment	Temperature 0-45°C / Humidity 30-70%Rh
Related Certification	RoHS、CE、BIS
Net Weight	22kg
Main Hardware	American TI AM3358 industrial grade CPU, American Xilinx Spartan-6 industrial grade FPGA
External Interface	Optical sensor, Encoder, Reverse and upside down control, Signal light alarm output, Serial number output control, External printing information selection
Support Language	Support more than 40 national languages (Chinese, English, Arabic, Danish, German, Russian, French, Finnish, Korean, Japanese, Spanish, Italian, etc.)

🔥 Applications

PET plastics



Packing carton



Medicine



Food packaging



Furniture and wood

🔥 Printing Samples

5X6	ABCDEFGH 12345 5X6
7X6	ABCDEFGH 12345 6X7
7X10	ABCDEFGH 12345 生产日期 10x7
9X8	ABCDEFGH 12345 8X9
9X11	ABCDEFGH 12345 年月日 11X9
11X11L	ABCDEFGH 12345 年月日 11X11
11X11B	ABCDEFGH 12345 11X11B
16X16L	ABCDEFGH 12345 16X16L
16X16B	ABCDEFGH 12345 16X16B
24X24L	ABCDE12345 24X24L
24X24B	ABCDE12345 24X24B
7X6(2lines)	QWERTYUIOP 生产日期:20210414 1234567890 生产批号:20210414
7X6(3lines)	QWERTYUIOP 生产日期:20210414 1234567890 生产批号:20220414 ABCDEFGHIJKLMN0P0123456789
LOGO	
Tower	
DM Codes	
Barcodes	

Codpad

Guangzhou Codpad e-tech Company Limited

<https://www.docod-group.com/> sales@docod.com.cn

market@docod.com.cn service@docod.com.cn WhatsApp:+86 139 2896 7650

Add: Building 2, NO.27, Hejing Road, LiWan District, Guangzhou, China